

5 HP. [3.7 KW] 3 PH  
50/60 HZ MOTOR

DISCHARGE OUTLET  
1.875 x 3 O.D.  
[48.00] x [76.00]

50 LB. [23 KG]  
TOTE (OPTIONAL)

.875 [22.00]  
MTG. HOLES (4)

75 LB. [34 KG]  
HOPPER (OPTIONAL)

SLIDE GATE  
(OPTIONAL)

GRIND ADJUSTMENT

ADJUSTABLE  
DECHAFFING  
ASSEMBLY

MOTOR  
CONTROL SWITCH

**NOTES:**

1. DIMENSIONS WILL BE INDICATED AS FOLLOWED, 1 [25.4]

ENGLISH (IN)

METRIC (MM)

**GPC-140 Specifications**


Motor: Heavy Duty (5) Five HP TEFC 3 Phase 60 HZ 208-230/460 VAC  
(1200 RPM) (50 HZ And Special Voltages Available)

Motor Starter: Magnetic Style With Dust Proof Enclosure

Weights: Net: 400 LBS (182 KGS) Shipping w/Crate: 500 LBS (228 KGS)

Production Capacity: 600 LBS (275 KGS) Per Hour - Fine Grind  
1000 LBS (455 KGS) Per Hour - Course Grind

Hopper Capacity: Approximately 75 LBS (34 KGS)

MATERIAL		USED ON UNIT		 <b>MODERN PROCESS EQUIPMENT, Inc.</b> <small>325 South Lake Avenue, Chicago, Illinois 60605</small>	DRAWN: RR DATE: 1/06/09 CHECKED:	SCALE: 8
PATTERN NO.		MPE			NAME OF PART: MODEL GPC-140 COFFEE GRINDER	PART NO.: GP-7606
REV.	CHANGE	DATE	BY			